PH-3100A Infrared Ray Type



Features

- Total 400W IR of Heating Power- Ensures the heat is saturates evenly and smoothly over multilayered PCBs allowing for fast manual soldering
- PCB Holders and Bottom-side supports included-allows for set up and use for preheating without the need for additional purchases of accessories.
- Wide Area Heating Design- The large area heating helps prevent the board from warping due to uneven heating.
- Designed for use with SD-3000II- This pre-heater is also designed for use with SD-3000II

Fast Efficient Pre-heater

- The pre-heater uses 2x 200W IR heaters and closed-loop control to enable fast and safety manual soldering
- The pre-heater is designed for multilayer PCB under Lead-Free solder with large heat sinks.

Example of use



Combined with when Soldering lead free



This pre-heater is also designed for use with the SD-3000II to prevent PCB warpage



Accessories



Specifications

● PCB Holders and Bottom-side supports included-allows for set up and use for preheating without the need for additional purchases of accessories.

● Heating Method: Infrared Heating System, 200w x 2

■ Temperature Setting Range: 100°C~230°C (Sensor Feed Back Method)
■ Voltage/Electricity: AC100V 50/60Hz AC200-230V 50/60Hz

Dimension: 350mm wide x 62mm high x 295mm deep

• Weight: 4Kgs

Dic Trading Co., ltd.

1-26-10, SEKIMACHI HIGASHI, NERIMA-KU

TOKYO 177-0052 JAPAN.

TEL:+81-3-3929-6800

FAX:+81-3-3929-7441

Web: www.denondic.co.jp

Manifacturer: Den-on Instruments Co.,ltd